



EASY WINDOW X PRODUCT CODE: 4-0110

PRODUCT DESCRIPTION

This 3.5 mil gloss clear vinyl is compatible with a variety of printing methods such as solvent, eco-solvent, and UV ink jet technologies. Excellent for use in point of purchase displays, trade show displays, and window graphics.

APPLICATIONS

- Point of purchase displays
- Trade show displays
- Window graphics

FEATURES AND BENEFITS

- Compatible with a variety of printing methods
- Licensed Air Flow Release Liner™ for easier and faster graphic applications
- Solvent acrylic removable adhesive

TECHNICAL DATA

Face Material	3.5-mil flexible vinyl
Color and Finish	Clear gloss
Adhesive	27, solvent acrylic removable adhesive
Liner	90# Licensed Air Flow Release Liner™

TYPICAL CHARACTERISTICS

Target Adhesion Values	<u>15 min.</u>	<u>24 hr.</u>
(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	30 oz.	40 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Durability	3 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

Dec-10

Form 108-01 (1/99)